

12/17/09

Invoice: A34600

Customer Code: 499609

SUNLIGHT SUPPLY, INC.  
5408 NE 88TH ST. BLDG A-101  
VANCOUVER, WA 98665

Dear Customer:

Enclosed for your use is a Material Safety Data Sheet (MSDS) which contains health and safety information on the DuPont Powder Coatings material listed at the top of page one.

This MSDS supercedes any previous MSDS you may have for the material.

Any person who sells or otherwise distributes a mixture or trade name product containing a chemical listed in 40 CFR 372.65 must provide written notice to the recipient with the first shipment each calendar year per section 313 of Title III, Superfunds Amendments and Reauthorization Act of 1986 (SARA).

The MSDS is supplied to you pursuant to these requirements. Please ensure that this information is available to all persons handling the material.

MSDSs are an integral part of the hazard communication and employee information and training programs required of employers under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

If you have any questions or require additional information in the use of this product, please contact us at (713)939-4000.

DuPont Powder Coatings U.S.A., Inc.

Enclosure

[R&D 4.203-1 07/99]

# MATERIAL SAFETY DATA SHEET

Product name: SKY WHITE  
Product code: PFW510S9055  
Product date: DEC 15 2009

Print date: 12/17/09

Page 1

---

## Section 1 - Product and Company Identification

Product Name: SKY WHITE

Company Identification: DuPont Powder Coatings  
9800 Genard Rd  
Houston, TX 77041-7624

Telephone/Fax: 713.939.4000 / 713.939.4025  
Chemtrec International (24hr): 703.527.3887 Collect  
Chemtrec USA (24hr): 800.424.9300  
Medical Emergency 800.441.3637

Product Class: COATING POWDER  
Product Number: PFW510S9

## Section 2 - Ingredient Information

Ingredient Name	CAS Number	Percent
TITANIUM DIOXIDE	013463-67-7	15 - 40
BARIUM SULFATE	007727-43-7	5 - 10
1,3,5-Triglycidyl Isocyanurate	002451-62-9	1 - 5
SILICA, AMORPHOUS	112926-00-8	1 - 5
ALUMINUM HYDROXIDE	021645-51-2	0.5 - 1.5
NUISANCE DUST	N/A	As generated

## Section 3 - Hazards Identification

Potential Health Hazards (powder mixture).

May cause skin and eye irritation. May cause irritation of the upper respiratory tract (nose, mouth and/or throat), resulting in sneezing coughing and sore throat. Long-term respiratory exposure exceeding exposure limits may damage the lungs, leading to impairment of lung capacity.

The acute and chronic health effect statements below are for the pure chemicals only, unless noted.

---

# MATERIAL SAFETY DATA SHEET

Product name: SKY WHITE  
Product code: PFW510S9055  
Product date: DEC 15 2009

Print date: 12/17/09

Page 3

-----  
Prolonged exposure could cause benign pneumoconiosis called Baritosis.  
(TITANIUM DIOXIDE)

Laboratory studies show that inhalation exposure to high levels (250 mg/kg) of Titanium Dioxide causes cancerous tumors in rats. This response occurs at lower exposure levels and may be due to the high levels overwhelming normal lung clearance mechanisms. The relevance of this data to humans is not significant where the TLV is observed.

#### MEDICAL CONDITIONS PRONE TO AGGRAVATION BY OVEREXPOSURE:

(1,3,5-Triglycidyl Isocyanurate)

Respiratory illness & dermatitis may be aggravated by excessive exposure.

(SILICA, AMORPHOUS)

Preexisting lung diseases may increase susceptibility to the effects of excessive amorphous silica dust exposure.

#### PRIMARY ROUTES OF ENTRY:

Inhalation, Dermal, or Ingestion

## Section 4 - First Aid Measures

#### EYE CONTACT

Flush eyes with cool water for 15 minutes, occasionally lifting lids to ensure thorough rinsing. Seek medical assistance.

#### SKIN CONTACT

Wash thoroughly with soap and water.

#### INHALATION

Remove from area to fresh air.

#### INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

## Section 5 - Fire Fighting Measures

MEC >/= 26g/m3 (see sec. 16)

#### EXTINGUISHING MEDIA

FOAM  CO2  DRY CHEMICAL  WATER FOG  DRY SAND

#### FIRE FIGHTING INSTRUCTIONS

Use fully protective equipment with self-contained breathing apparatus. The material has a flammability rating similar to a water-borne coating. Dust generated from this product during handling may create a fire and/or explosion hazard. Minimize dusting during use. Keep all equipment clean and properly grounded to avoid static electricity discharge.

## Section 6 - Accidental Release Measures

-----

# MATERIAL SAFETY DATA SHEET

Product name: SKY WHITE  
Product code: PFW510S9055  
Product date: DEC 15 2009

Print date: 12/17/09

Page 5

-----  
recommended.

EYE PROTECTION: Goggles or safety glasses w/side shields recommended.  
OTHER PROTECTIVE EQUIPMENT: Protective overalls recommended. Remove and wash soiled clothing.

## Section 9 - Physical and Chemical Properties

Spec. Grav., ASTM D5965-96,C:1.69

## Section 10 - Stability and Reactivity

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes may contain CO, CO2, NO2 or other Nitrogen compounds.

## Section 11 - Toxicological Information

Route	Species	Exposure and Dose
TITANIUM DIOXIDE Oral	Rat, adult	LD50 9500. mg/kg
1,3,5-Triglycidyl Isocyanurate Oral	Rat, adult	LD50 440. mg/kg

## Section 12 - Ecological Information

None known

## Section 13 - Disposal Considerations

Manage or dispose in accordance with local, state and federal regulations.

## Section 14 - Transport Information

Not Regulated

## Section 15 - Regulatory Information

-PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
1,3,5-Triglycidyl Isocyanurate	002451-62-9	< 5

-----

