



The Chemical Company

704570

Safety Data Sheet

1600 X-CLUDE®

Revision date : 2009/12/18

Version: 1.0

Page: 1/8

(30472312/SDS_CPA_US/EN)

1. Product and Company Identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Registrant:
Whitmire Micro-Gen Research Laboratories, Inc.
3568 Tree Court Industrial Blvd.
St. Louis, MO 63122

Substance number: 000000414099
Synonyms: Pyrethrins + piperonyl butoxide + n-octyl bicycloheptene dicarboximide

2. Hazards Identification

Emergency overview

CAUTION:
KEEP OUT OF REACH OF CHILDREN.
KEEP OUT OF REACH OF DOMESTIC ANIMALS.
Avoid inhalation of mists/vapours.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.
Flammable Liquid
Aerosol container contains flammable gas under pressure.

See Product Label for additional precautionary statements.

State of matter: liquid
Colour: beige to yellow
Odour: characteristic

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Relatively nontoxic after single ingestion. Slightly toxic after short-term skin contact.

Irritation / corrosion:

May cause slight but temporary irritation to the eyes. Contact may result in skin irritation.

Sensitization:

Safety Data Sheet

1600 X-CLUDE®

Revision date : 2009/12/18
Version: 1.0

Page: 3/8
(30472312/SDS_CPA_US/EN)

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Evacuate area of all unnecessary personnel. Contain contaminated water/firefighting water. Do not allow to enter drains or waterways.

6. Accidental release measures

Personal precautions:

Take appropriate protective measures. Clear area. Shut off source of leak only under safe conditions. Extinguish sources of ignition nearby and downwind. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions:

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities. This product is regulated by CERCLA ('Superfund').

Cleanup:

Dike spillage. Pick up with suitable absorbent material. Spilled substance/product should be recovered and applied according to label rates whenever possible. If application of spilled substance/product is not possible, then spills should be contained, solidified, and placed in suitable containers for disposal. After decontamination, spill area can be washed with water. Collect wash water for approved disposal.

7. Handling and Storage

Handling

General advice:

RECOMMENDATIONS ARE FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS. PESTICIDE APPLICATORS & WORKERS must refer to the Product Label and Directions for Use attached to the product. Provide good ventilation of working area (local exhaust ventilation if necessary). Keep away from sources of ignition - No smoking. Keep container tightly sealed. Protect against heat. Handle and open container with care. Do not open until ready to use. Once container is opened, content should be used as soon as possible. Provide means for controlling leaks and spills. Follow label warnings even after container is emptied. The substance/ product may be handled only by appropriately trained personnel. Avoid all direct contact with the substance/product. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Wear suitable personal protective clothing and equipment.

Protection against fire and explosion:

Aerosol container contains flammable gas under pressure. The relevant fire protection measures should be noted. Fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat. Ground all transfer equipment properly to prevent electrostatic discharge. Electrostatic discharge may cause ignition.

Storage

General advice:

Protect containers from physical damage. Store in a cool, dry, well-ventilated area. Avoid all sources of ignition: heat, sparks, open flame. Store protected against freezing.

Storage incompatibility:

General advice: Segregate from incompatible substances. Segregate from foods and animal feeds. Segregate from textiles and similar materials.

Storage stability:

May be kept indefinitely if stored properly. If an expiry date is mentioned on the packaging/label this takes priority over the statements on storage duration in this safety data sheet.

Safety Data Sheet

1600 X-CLUDE®

Revision date : 2009/12/18
Version: 1.0

Page: 5/8
(30472312/SDS_CPA_US/EN)

9. Physical and Chemical Properties

Form:	aerosol	
Odour:	characteristic	
Colour:	beige to yellow	
pH value:	6 - 7	
Boiling range:	approx. 100 °C	Information applies to the solvent.
Density:	0.995 g/cm ³	(approx. 20 °C)
Solubility in water:		dispersible

10. Stability and Reactivity

Conditions to avoid:

Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme temperatures. Avoid prolonged exposure to extreme heat. Avoid contamination. Avoid electro-static discharge.

Substances to avoid:

No substances known that should be avoided.

Hazardous reactions:

The product is chemically stable.

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated., Prolonged thermal loading can result in products of degradation being given off.

Thermal decomposition:

Possible thermal decomposition products:

carbon monoxide, carbon dioxide, nitrogen dioxide, nitrogen oxide

Stable at ambient temperature. If product is heated above decomposition temperature toxic vapours may be released. To avoid thermal decomposition, do not overheat.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

11. Toxicological information

Acute toxicity

Oral:

Type of value: LD50

Species: rat

Value: > 5,000 mg/kg

Dermal:

Type of value: LD50

Species: rabbit

Value: > 2,000 mg/kg

Irritation / corrosion

Skin:

Species: rabbit

Result: non-irritant

Sensitization:

Species: guinea pig

Result: Caused skin sensitization in animal studies.